

## IN THE CLAIMS

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1. (Previously Presented) An AGC (automatic gain control) device in an OFDM (orthogonal frequency division multiplexing) system, comprising:
  - a RF (radio frequency) unit for controlling a gain of an input signal;
  - a first energy calculator for calculating an energy of output of the RF unit ;
  - a first accumulator for accumulating the energy calculated by the first energy calculator, finding a mean value thereof, and outputting the mean value;
  - a second accumulator for accumulating output of the RF unit, calculating a mean value of the accumulated output and outputting the mean value as a DC offset ;
  - a second energy calculator for calculating an energy of the DC offset outputted by the second accumulator;
  - a first subtractor for subtracting the energy of the DC offset of the input signal output by the second energy calculator from the energy of the input signal output by the first accumulator; and
  - a second subtractor for subtracting a specific reference value established for AGC from an output of the first subtractor, and performing feedback of an output of the second subtractor for AGC to the RF unit.
2. (Original) The AGC device of claim 1, wherein the energy calculation for AGC is performed in a training sequence interval of the input signal.
3. (Original) The AGC device of claim 2, wherein the energy calculation is performed for each interval of 16 samples when the training sequence interval is a short training sequence interval.

4. (Original) The AGC device of claim 2, wherein the energy calculation is performed for each interval of 64 samples when the training sequence interval is a long training sequence interval.

5. (Original) The AGC device of claim 1, wherein the first and second energy calculators find a summation of the square of the input signal, and output a result as an energy.

6. (Previously Presented) The AGC device of claim 5, wherein the energy  $\hat{Energy}$  output by the first accumulator is given as

$$\hat{Energy} = \frac{1}{N} \sum_{n=1}^N [Si(n)^2 + Sq(n)^2] + [Di^2 + Dq^2]$$

wherein I and Q values of the training sequence input to the first energy calculator are expressed as the summation of ideal signals  $S_i$  and  $S_q$  (i.e., without DC offsets) and DC offsets  $D_i$  and  $D_q$ , a mean value of the  $S_i$  and  $S_q$  is zero in a specific interval  $N$ , and the  $D_i$  and  $D_q$  are constants.

7. (Original) The AGC device of claim 6, wherein the energy  $E$  output by the second energy calculator is expressed by the equation

$$E = D_i^2 + D_q^2.$$

8. (Original) The AGC device of claim 7, wherein the energy  $E$  output by the subtractor is expressed by the following equation and represents an ideal signal without DC offsets

$$\hat{Energy} = \frac{1}{N} \sum_{n=1}^N [Si(n)^2 + Sq(n)^2].$$

9. (Previously Presented) The AGC device of claim 1, further comprising a dB converter provided between the first subtractor and the second subtractor, the dB converter converting an output of the subtractor into a dB value.

10. (Previously Presented) The AGC device of claim 1, further comprising:

an A/D (analog-to-digital) converter for converting the input signal into a digital signal, and inputting the digital signal to the first energy calculator and the second accumulator; and

a D/A (digital-to-analog) converter for converting an output of the second subtractor into a digital signal, and outputting the digital signal to the RF unit.

11. (Previously Presented) An AGC (automatic gain control) method in an OFDM (orthogonal frequency division multiplexing) system, comprising:

(a) performing coarse AGC through a DC offset cancellation in a short training sequence interval when an input signal is detected, the AGC being performed by subtracting an energy of the DC offset from an energy of the input signal and using an energy of the DC offset cancelled ideal signal, the DC offset being a mean value of the input signal accumulated for the specified period;

(b) performing a coarse frequency offset search and cancellation in the short training sequence interval;

(c) performing fine AGC through a DC offset cancellation in a long training sequence interval, the AGC being performed by subtracting the energy of the DC offset from the energy of the input signal and using the energy of the DC offset cancelled ideal signal; and

(d) performing a fine frequency offset search and cancellation in the long training sequence interval.

12. (Original) The AGC method of claim 11, wherein the AGC in (a) is performed for each unit of 16 samples in the short training sequence interval.

13. (Original) The AGC method of claim 11, wherein the AGC in (c) is performed for each unit of 64 samples in the long training sequence interval.

14. (Previously Presented) The AGC method of claim 11, wherein (b) is performed in a final three repeated intervals of the short training sequence.

15. (Cancelled)